

APPLICATION FOR UNITED STATES PATENT

SNOWSHOE WITH TWO DEGREES OF ROTATIONAL FREEDOM

S P E C I F I C A T I O N

Background of the Invention

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2

the toe end of the snowshoe in the snow. Such pivoting has been achieved by supporting the boot footbed on support straps, as in Atlas Snow-Shoe Company's Patents Nos. 5,440,827, 5,687,491 5,699,630, and 6,256,908; and has also been accomplished with
5 simple pivot bars, as in Patent No. 5,946,829, for example.

When traversing a side hill path, a snowshoe user needs another degree of freedom for comfort and safety in full terrain engagement -- rotation about a "roll" axis, which can be described as rotation within the frontal plane. This should be a
10 limited freedom of movement, with spring loading effective to return the snowshoe to the normal position and to resist the roll rotation of the snowshoe more strongly as the degree of roll rotation increases. Such a freedom of movement will allow the snowshoe to tip along the roll axis when the user plants the
15 snowshoe down against terrain which is uneven and particularly, terrain which slopes from one side to the other. The snowshoe would therefore follow the terrain and be planted more firmly, while also increasing comfort and safety to the user and reducing ankle and foot stress.

20 U.S. Patent No. 5,946,829 discloses a snowshoe which is aimed at the above goal. The snowshoe has a frame of a convoluted configuration, not contiguous in a closed loop around the frame, and in which inner members of the frame near the rear turn forward to form a flexible, spring-biased mounting by frame

twisting that allows some degree of torsional freedom along the roll axis, i.e., in the frontal plane. That type of snowshoe frame has some disadvantages compared to the present invention described below.

5

Summary of the Invention

10 The invention described herein achieves a second degree of rotational freedom, for movement within the frontal plane or about the roll axis of the snowshoe, in an efficient manner which still provides the benefit of a relatively simple and straightforward snowshoe design. This second degree of freedom is combined with the typically permitted rotation about the traverse or pitch axis, also preferably spring-biased toward a pre-selected "zero" position. At the same time, the
15 configuration of the invention substantially prevents any rotation of the snowshoe in the yaw direction, about a vertical axis, which rotation would tend to be unstable and awkward and would cause discomfort and instability.

20 The two degrees of rotational freedom can be achieved in several different ways. As one example, the footbed of the snowshoe harness can have a mounting which includes a transverse horizontal pivot, preferably with spring-biased torsional resistance tending to return a pivot frame back to a prescribed relationship with the snowshoe frame. An additional pivot can be

made between the footbed and the pivot frame, via a roll pivot axis at the middle of the pivot frame, permitting the desired rotation in the frontal plane. Leaf springs or a torsion rod can be used as a spring to bias this second degree of rotational freedom back toward the normal, undeflected position. Coil springs can be used for the zero-biasing of the footbed if desired.

Another configuration allowing two degrees of freedom uses strap suspension, somewhat similar to the front harness binding shown in the above Atlas Snow-Shoe Company patents. In this case, however, the support straps support a longitudinally extending rod or mounting device along a roll axis rather than supporting the footbed itself. The footbed is then secured to the rod or other pivot mounting so as to allow for the desired roll rotation. The rod can be a torsion rod, providing the needed bias. In this way, a simple support mechanism provides two degrees of spring-biased rotational freedom.

Another configuration for achieving the desired two degrees of freedom utilizes a pair of torsion arms secured to the normal peripheral snowshoe frame, these arms extending generally parallel to the snowshoe frame and to one another and being positioned just inwardly of the frame members. The arms have a tightly biased flexibility, such that if a torsion rod or pivot rod is connected between their forward tips, some degree of

biased roll rotation is permitted. The rod extending between these arms provides the normal pitch rotation, and if this is provided as a torsion rod, the desired biasing is included.

A variation of the above is achieved in a molded snowshoe, preferably of fiber-reinforced plastic. Integrally molded arms extend in a forward direction within the snowshoe body, cantilevered from back ends of the arms. The front ends of the arms allow spring-biased roll freedom when a footbed is secured via these forward arm ends.

Another form of the invention has a snowshoe frame which can twist and rotate at certain points to allow footbed tilt relative to terrain.

It is therefore among the objects of the invention to provide a relatively simple and reliable connection between the user's boot and a snowshoe, whereby two degrees of freedom of movement of the snowshoe relative to the user's boot are permitted, these two degrees of freedom being rotation about the normal pitch axis and also about a roll axis, preferably with both axes biased toward a normal position. These and other objects, advantages and features of the invention will be apparent from the following description of Preferred Embodiments, considered along with the drawings.

Description of the Drawings

Fig. 1 is a schematic prospective diagram indicating possible degrees of rotational freedom in a snowshoe having a frame of conventional construction.

5 Fig. 2 is a plan view showing a snowshoe frame with one form of boot binding support affording two degrees of rotation of freedom, in pitch and roll directions.

Fig. 2A is a side elevation view of the snowshoe of Fig. 2.

10 Figs. 3 and 3A are plan and side elevation views showing another structural configuration for affording the desired two degrees of rotational freedom in a snowshoe.

Fig. 3B is a schematic perspective view showing a molded snowshoe providing the desired two degrees of freedom, in a manner similar to Figs. 3-3A.

15 Figs. 4 and 4A are an exploded view in perspective and a side cross sectional elevation view illustrating a pivot frame and footbed for implementing a further form of the invention to produce two degrees of rotational freedom.

20 Figs. 5, 5A and 5B are exploded perspective and sectional views indicating a further form of the invention, with Figs. 5A and 5B showing flexing of the footbed within the second degree of rotational freedom.

Figs. 6 and 6A are additional exploded perspective and sectional schematic views indicating a further form of the

invention for achieving two degrees of rotational freedom.

Figs. 7 and 7A are further exploded perspective and cross-sectional views, indicating another variation of the invention for achieving the desired degrees of freedom.

5 Figs. 8 and 8A are exploded perspective and schematic cross-sectional views showing still another form of snowshoe footbed pivot arrangement according to the invention.

Figs. 9 and 9A are views generally similar to Figs. 8 and 8A, but show a variation.

10 Figs. 10 and 10A are exploded perspective and schematic sectional views showing a further variation of Fig. 8.

Figs. 11, 11A and 11B are similar setup drawings showing a further variation.

15 Figs. 12, 12A and 12B are additional exploded perspective and cross-sectional views indicating another structural configuration of the invention for achieving the desired two degrees of rotational freedom.

20 Figs. 13, 13A and 13B are further exploded perspective and schematic sectional views, showing a further variation affording the desired degrees of freedom in accordance with the invention.

Figs. 14, 14A and 14B are exploded perspective and schematic sectional views showing a further form of snowshoe footbed suspension providing the desired degrees of freedom.

Figs. 15, 15A, 15B and 15C are views showing a further

variation of the invention, with Fig. 15C schematically indicating a desired level for the rotational axis of the second degree of freedom relative to the user's foot.

Figs. 16, 16A and 16B show a further variation of a two-axis snowshoe footbed support, in this case providing the axis of the second degree of freedom at an approximate optimal location.

Figs. 17, 17A and 17B show another variation, wherein a snowshoe frame provides for limited rotation on the roll axis.

Fig. 18 is a perspective view from the bottom showing a molded plastic composite snowshoe having curved metal rails insert molded into the plastic material.

Fig. 19 is an enlarged view showing a portion of the snowshoe of Fig. 18, and indicating a footbed secured by **WORD** cables from the molded composite snowshoe body.

Fig. 20 is a perspective view showing the upper side of the molded composite snowshoe of Figs. 18 and 19.

Fig. 21 is a schematic view in perspective showing a portion of a snowshoe and indicating a cable binding or footbed suspension in one embodiment.

Fig. 22 is a bottom perspective view schematically showing a portion of a snowshoe and indicating another embodiment of a cable suspension.

Fig. 23 is schematically similar to Fig. 22, showing a further embodiment.

Figs. 24A, 24B, and 24C are schematic diagrams indicating frontal plane rotation of the cable binding, i.e. rotation about a roll axis.

Fig. 25 is a schematic diagram in perspective, demonstrating resistance of cable binding embodiments of the invention to rotation about the yaw axis.

Fig. 26 is a schematic perspective view showing a portion of a snowshoe bottom and indicating a further embodiment of a cable binding or suspension.

Fig. 27 is a perspective view similar to 26, indicating a further embodiment.

Fig. 28 is a schematic view showing a portion of a cable suspension to demonstrate the principle involved.

Fig. 29 is a schematic view similar to Fig. 28, but showing cables passing through a single hole.

Description of Preferred Embodiments

Fig. 1 indicates conceptually the framework and principles of the invention, showing potential rotational axes of a snowshoe 10 relative to the user's boot, or to a footbed 12 to which the user's boot is secured. These axes of rotation, as mentioned above, are a transverse horizontal axis 14, or pitch axis, regarding potential rotation in the sagittal plane; the longitudinal horizontal axis 16 or roll axis, pertaining to

rotation in the frontal plane; and the vertical axis or yaw axis 18, regarding rotation within a horizontal plane. This latter rotation is wholly undesirable and leads to instability in use of the snowshoe. Rotation about the yaw axis is to be avoided as
5 nearly as possible.

A rotation about the pitch axis, within the sagittal plane, is desirable as discussed previously, and has been provided for in numerous previous snowshoes of Atlas Snow-Shoe Company and others. In the schematic perspective view of Fig. 1, this
10 rotation is indicated as occurring via a bar or pivot pin 20 which permits rotation of the footbed 12 relative to the snowshoe frame 22. Such rotation has been provided on Atlas snowshoes via straps which secure the footbed to the frame, establishing the desired limited rotation and also a biasing force to return the
15 footbed and snowshoe to a desired "zero" relative position. As discussed above, limited rotation about the roll axis is also desirable but has seldom been provided on snowshoes. Patent No. 5,946,829 provides for some degree of rotation approximately on this axis, but this is accomplished via a special snowshoe frame
20 which does not comprise a uniform peripheral frame 22 secured together at the rear (as at 24 in Fig. 1) as typical of frame and flexible deck type snowshoes. The cited patent may also provide for some rotation in the undesirable direction, about the yaw axis 18.

Figs. 2 and 2A show one embodiment of the invention for permitting the desired two degrees of rotational freedom without any substantial freedom of movement about the yaw axis. In this form of the invention, the snowshoe 25 has a snowshoe frame 26 about which straps 28, 30 are wrapped in the manner shown, which is similar to what is shown in Atlas Snow-Shoe Company Patent No. 5,440,827, for example. These straps 28, 30 can comprise a single strap. In this case the straps are spread apart widely in the central portion of the snowshoe's boot harness area, for connection to a rod 32 as shown. See Figs. 2 and 2A. The rod 32 may be rigidly connected to the straps 28 and 30, with the rod having torsional flexibility such that a footpad mounted near the center portion of the rod is afforded some degree of rotation along the center line of the rod. This provides the roll axis rotation described, preferably affording roll rotation of about 10° to 15° (or about 10° to 20°) each direction. Otherwise, the rod 32 can be mounted in bushings 34 at both ends, affording free rotation of the rod, with limitation to movement and biasing back to the "zero" position accomplished by other structure, such as coil or leaf springs.

Fig. 2A shows the snowshoe 25 in elevation, indicating that the rod 32 has a zero position in which it is inclined forwardly/downwardly, to establish the pitch-axis bias position such that the toe end of the snowshoe is urged downwardly.

Figs. 2 and 2A show that the roll axis rotation (frontal plane rotation) of the snowshoe relative to the boot is achieved by rotation about the rod 32, while pitch-axis rotation (about the sagittal plane) is provided by the twisting of the binding straps 28 and 30, which effects a spring-like deflection of the snowshoe frame in the preferred situation in which the straps 28, 30 are not stretchable. Undesirable rotation about the yaw axis is resisted by the triangular geometry shown, by which the rod 32 is secured to the snowshoe frame via two triangles established with the straps 28 and 30.

In Figs. 3 and 3A, a snowshoe 35 supports a footbed 36 for a user's boot 38 in a different manner, but again achieving two degrees of rotational freedom, about the pitch axis and the roll axis. Here, the snowshoe frame 40 supports a pair of torsion arms 42 via frame joint inserts or collars 44 (or other mechanical means) rigidly connected to the frame. The torsion arms 42 can be of metal or reinforced plastic, capable of deflecting sufficiently to allow the desired degree of roll-axis rotation, with biased return to normal position. Note that the left and right torsion arms 42 can deflect independently. A pivot rod 46 secured to and extending between ends of the torsion arms allows sagittal plane rotation, about the pitch axis. This rod can be freely rotating relative to the arms, or constructed as a torsion rod and rigidly secured to the arms. The latter

will provide a return force to the normal pitch position. This rod can be either metal or elastomer construction.

Fig. 3B shows a variation of what is shown in Figs. 3 and 3A, for a molded plastic composite snowshoe 50. In this case, the snowshoe has no peripheral frame in the sense of that provided in Figs. 2-3A, and has no flexible decking suspended on such a peripheral frame, but instead the molded composite snowshoe 50 provides both a snowshoe decking 52 and, in essence, a frame which adds the needed rigidity (stiffener ridges can be included, not shown). The snowshoe 50 is integrally molded to provide a pair of torsion arms 54 which deflect angularly downwardly or upwardly and which function essentially the same as the torsion arms 42 in Figs. 3 and 3A. As shown, the torsion arms 54 extend forward from integral connection areas 56 to forward ends 58 of the arms, where they support a transverse rod 60 which can be similar to what is shown at 46 in Fig. 3. The rod 60 can provide for pitch-axis pivoting, as in the earlier embodiment, and it can also be a torsion rod which provides the needed spring-like biasing force to return the snowshoe back to a desired normal pitch position relative to the binding or boot platform (not shown in Fig. 3B).

Fig. 4 shows another preferred embodiment for achieving the two degrees of rotational freedom in a snowshoe binding as desired. Here, the two degrees of rotational freedom are

achieved by a pivot frame 65, to which is pivotally secured a footbed platform 66. The snowshoe and its frame are not shown in Fig. 4; the front of the snowshoe is generally to the left in Fig. 4 as shown by the arrow 68. The pivot frame 65 is secured to the snowshoe frame at end points 70, which may be by rigid attachment or via a pivot. If a rigid attachment, the pivot frame 65 acts as a torsion bar, providing for limited rotation about the pitch axis, within the sagittal plane, and providing a return force. The pivot frame 65 includes a central pivot support with upturned flanges 72 as shown, for receiving the pivotal footbed via a torsion rod 74. The torsion rod can be fixed to one of the flanges 72, at an aperture 75, as by welding, spline or other connection, and to the footbed aperture 76, on the opposite side. In this way, the footbed is supported for pivoting movement along the roll axis (in the frontal plane), and the length of the torsion rod 74 is available for twisting to provide the spring action tending to return the snowshoe to the "zero" position relative to the footbed and the user's boot. Fig. 4A shows this arrangement in a side elevation cross sectional view.

Fig. 5 shows another configuration for achieving the same objective. In this form of the invention, a snowshoe frame 80 supports a binding strap or straps 82, in substantially the manner in which Atlas Snow-Shoe boot bindings have been supported

previously for rotation along on the pitch axis, as shown, for example, in Atlas Patent No. 5,440,827.

As shown in Figs. 5-5B, the snowshoe in this embodiment achieves the desired second degree of rotational freedom about the roll axis through use of rubbery elastomeric bushings 84. The snowshoe's front cleat 86, which also provides or is connected to a footbed for the user's boot, is secured to the binding strap or straps 82 via these elastomeric bushings 84 as indicated in the exploded view of Fig. 5. This provides for side to side tipping of the snowshoe, i.e. deflection about the roll axis, through deformation of the bushings 84. The transverse sectional elevation view of Fig. 5A shows the footbed/front claw 86 in the normal position, while the similar cross sectional view of Fig. 5B shows the footbed and the snowshoe in a position of maximum roll-axis rotation to one side. This allows the snowshoe to follow sloping terrain, i.e., a side hill condition, without over-stressing the user's foot, ankle and leg.

Figs. 6 and 6A show another arrangement, essentially a variation of Fig. 5 and also incorporating some of the features of Figs. 4-4A. In this arrangement, a pivot frame 88 is secured to the opposing bars of a peripheral frame (not shown), and this pivot frame can be mounted for rotation about the pitch axis (through the length of the pivot frame 88), with biasing restraint provided by appropriate forms of springs or other

springable deflection devices, or the pivot frame can be fixed to the snowshoe frame, serving as a torsion bar as described relative to Fig. 4.

In either event, the footbed platform 90 of this assembly, which can also be a front claw as in Fig. 5, is secured to the pivot frame 88 by elastomeric bushings 92 as in Fig. 5. These are shown as being secured by a bolt and nut 94, 96, through a central hole 97 in the pivot frame. As an alternative, the bushings 92 could be replaced with compression springs.

Fig. 6A is a transverse cross sectional view showing deflection of the foot platform 90 about the roll axis, i.e., within the frontal plane. As shown in this schematic view, recesses 98 in the sides of the footbed 90 serve as rotation guides, these recesses riding over the pivot frame 88 and preventing yaw-axis rotation. The footbed platform 90 and pivot frame 88 are shown at maximum relative frontal plane rotation in one direction in Fig. 6A.

Figs. 7 and 7A show another preferred embodiment of the invention, in a variation of Fig. 6. Orientation relative to the snowshoe is the same. In this arrangement the pivot frame 100 takes a different form, but still is secured to the snowshoe frame (not shown) in a manner as described above, but with pivoting connections at left and right.

Here, the pivot frame has pivot support flanges 102, on

which a special footbed 104 is pivotally mounted via pivot ears 106. The footbed preferably is formed integrally of a single piece of metal, with left and right spring leaves 108 as shown. These, as indicated in the transverse sectional view of Fig. 7A, act as springs bearing down against the platform 110 of the pivot frame, tending to return the footbed platform 104 to the central, undeflected state about the roll axis 112 as shown in Fig. 7A.

Figs. 8 and 8A show a further variation on the basic operation of several of the previously described embodiments. The orientation of the components in Fig. 8 is the same as that in Figs. 6 and 7, and Fig. 8A is a cross section similar to Figs. 6A and 7A. Here, the modified pivot frame 112 (secured to the snowshoe frame, not shown, in a manner as described above) has a pair of upstanding pivot ears 114 to pivotally support a foot bed or foot box 116. This pivotal connection provides for rotation about the roll axis, similar to what is described above, but in this case the spring biasing toward the normal position is achieved in a different way. One or more coiled torsion springs 118 are secured about the pivot pin or rivets 120, so as to spring-bias the rotatable footbed or foot box 16 toward the centered position. One way of anchoring the ends of the spring 18 is to place them underneath each of a pair of frame-integral fingers 122 as shown in Figs. 8 and 8A. The center 124 of the coiled torsion spring 118 passes around the rivet 120. On left

or right tilting of the platform 116, one end or the other of the spring 118 is deflected downwardly.

The footbed or foot box 116 may be provided with holes 126, for access to the inner ends of the rivets 120 during manufacture.

Figs. 9 and 9A show schematically another embodiment of a two degrees of freedom binding according to the invention, similar in principle to Fig. 8 but achieving the spring biasing force in a different way. In Fig. 9 a pivot frame 130 is somewhat similar to the frame 112 in Fig. 8, and may be secured to the snowshoe frame in the same manner as in generally similar earlier described embodiments. The front of the snowshoe is again to the upper left in the drawing, as indicated by the direction arrow 132.

In this form of the invention the footbed or foot box 134 is again mounted for roll-axis pivoting on pivot support ears 136 and 138 of the pivot frame. In this case, the foot box 134 has left and right spring mounts or connections 140, to which coiled tension springs 142 are secured. The opposite ends of these springs are secured to spring mounts 144 on the pivot frame, as indicated in Fig. 9 and as shown in the transverse sectional view of Fig. 9A. These tension springs are afforded movement by slots 146 in the pivot frame, and they are shown in a deflected position, at approximate maximum tipping of the footbed 134

relative to the snowshoe frame, in Fig. 9A. It is seen from Fig. 9 and 9A that the tension springs 142 tend to return the snowshoe and boot platform or footbed 134 back to a normal position of alignment.

5 Figs. 10 and 10A show another variation on a construction similar to Figs. 6 through 9, in which a footbed component 148 is again connected to a pivot frame 150. Here, the spring action biasing the footbed 148 back to normal position along the roll axis is provided by leaf springs 152 integral with the footbed or
10 boot platform 148. The schematic transverse sectional view of Fig. 10A shows rotational deflection in one direction about the roll axis, in which the left leaf spring 152 is deflected and exerts a force tending to return the footbed 148 back to normal relationship with the pivot frame 150.

15 Figs. 11, 11A and 11B show another scheme for achieving the second degree of rotational freedom, utilizing a pivot frame 155 which has ends 156 adaptable for securing to a snowshoe frame in the same manner as described for Figs. 6-10. In this form of the invention, a coiled torsion spring and metal wire unit 158
20 provides the spring-biasing force to return a footbed 160 back to normal position, generally parallel to the pivot frame 155. The footbed 160 can have a stamped bridge 162 that is secured to the central area of the spring and metal wire component 158. This could be by welding, for example. The spring/metal wire element

158 is in turn connected to the pivot frame 155, and this can be via integral tabs 164 of the pivot frame that receive angled ends 166 of the metal wire element by. Figs. 11A and 11B show undeflected and maximum deflected positions of the pivot frame 155 relative to the boot footbed 160. The spring/metal wire element 158 actually supplies the pivot for the footbed, not requiring an additional pivot rod. In the maximum deflected position as in Fig. 11B, the footbed edge engages against the pivot frame as a stop.

Figs. 12-12B show another form of apparatus for obtaining the second desired rotational degree of freedom. The front of the snowshoe is again upper left as indicated by the direction arrow 170. The normal sagittal plane rotation (about the pitch axis) is achieved by a rod or pivot pin 172 extending across the snowshoe and connected to the frame. Pitch is controlled by an appropriate form of biasing spring or elastic element, not shown. The roll-axis freedom of movement is achieved in this case by elastomeric bushings 174 which engage against the vertical stem portion 176 of a generally T-shaped footbed 178. The elastomeric bushings 174 can be replaced by steel compression springs if desired. The assembled unit is shown schematically in Figs. 12A and 12B, the first figure showing the footbed in undeflected position relative to the pivot rod 172 and the second figure showing full deflection to one side. The bushings (or springs)

174 make a sandwich with the planar footbed stem 176 and the elastomeric material is deformed elastically in Fig. 12B, allowing side tipping or roll-axis rotation between the footbed and the pivot shaft 172, which remains aligned with the snowshoe frame. As can be seen in Figs. 12 and 12B, the footbed 178 has slots 180 in left and right depending flanges 182, and these are positioned to saddle the pivot rod 172. Thus, the slots act as guides for the footbed member when rotating about the roll axis, and they prevent undesirable yaw axis rotation, i.e. rotation within the generally horizontal plane between the user's boot and the snowshoe.

Figs. 13-13B show another form of the invention for achieving footbed rotation about the pitch axis and the roll axis. In this arrangement, a bent torsion rod 185 provides for the usual pitch rotation, the rod having ends 186 journalled for rotation in bearing brackets 188 secured to the snowshoe, whether the snowshoe is formed of a frame with flexible decking or comprises a molded composite snowshoe. The rod 185 is fixed to a boot footbed 190 at a front or rear position, such as at points 192 and 193. At points 194 at left and right, however, the footbed has an integral sleeve connected around the rod but not fixed to the rod. This allows some twisting of the rod to afford some rotation about the roll axis 196 when needed, as shown in the transverse sectional views of Figs. 13A and 13B. Fig. 13A

shows the flat, undeflected position in which the entire rod and the footbed lie in approximately the same plane. In Fig. 13B the snowshoe 198 has been placed on uneven or sloping terrain, such as in a sidehill condition, and the snowshoe has tipped relative to the footbed 190. The rod 185 has twisted so as to allow the snowshoe's bearing bracket 188 to move downwardly while still being journalled onto the rod end 186.

Figs. 14-14B show another variation which is in theory quite similar to the embodiment of Fig. 12. In Fig. 14 the front of the snowshoe is to the lower right, as indicated by the arrow 200. A front claw and footbed 202 is secured on a pivot rod 204 which provides the normal sagittal-plane rotation (about the pitch axis), this rod being secured to the snowshoe for rotation and being biased toward normal in a manner as described above.

The front claw/footbed assembly has integral side members 206 which include slots 208, these members also serving as claws in a preferred embodiment. As in the arrangement of Fig. 12, the slots 208 ride over the rod 204 and provide a guide for roll-axis rotation, also preventing vertical-axis (yaw) rotation. A stretchable membrane comprising an elastomeric pad 210 is assembled below the pivot rod 204 as shown in the exploded view of Fig. 14 and also shown in the schematic transverse elevation views of Figs. 14A and 14B. Rivets 212 and rivet backing washers 214 secure this assembly together in a sandwiched arrangement.

Figs. 14A and 14B show that when roll-axis rotation occurs, the elastomeric pad 210 provides flexibility while still biasing the assembly back to normal position, thus the rod 204 (and snowshoe) is allowed to tip relative to the footbed 202.

5 Figs. 15-15C show another form of the invention and a different theory of pivoting. Fig. 15C shows a foot 220 and indicates the most desirable location for roll-axis pivoting, i.e. about a pivot axis 222 located approximately at the ankle. This is for maximum comfort and safety and minimum stress to the snowshoe user. This desired or theoretical pivot axis 222 is
10 also seen in Figs. 15A and 15B. In Fig. 15 a pitch-axis rotation member 224 somewhat similar to the pivot frames shown in earlier embodiments is secured for rotation on the snowshoe, via ends 226 of this component. The typical sagittal plane rotation is
15 achieved in this way, and can be biased back to zero position by springs or elastomeric members. In this case, however, the roll-axis rotation is achieved via a footbed 226 having an arcuate bottom surface 228, for sliding or ball-bearing rotation in a concave arcuate saddle or recess 230 formed in the cross member
20 224. A bearing race can be provided at 232. To secure the footbed 226 to the cross member 224, a bolt 234 and special, arcuate-bottomed nut 236 can be provided, to seat in an appropriately shaped recess 238 on the upper side of the footbed 226. This provides for roll-axis pivoting about a high axis of

rotation, approximately at the location 222 shown in Figs. 15A and 15B, indicating normal position and sidehill position. Bias back to the zero position is not shown but could be achieved with springs.

5 Figs. 16-16B show another arrangement for providing a high axis of roll rotation, following the same theory as in Fig. 15. Again, the front of the snowshoe is down into the right in Fig. 16. A footbed frame 240 is connected to a frontal rotation frame 242, and this can be via rivets or bolts and nuts 244, 246. The
10 user's boot is placed on the footbed 240 and, as shown in Figs. 16A and 16B, the snowshoe is permitted to assume a tipped position for sidehill situations. A transverse rod or cross number 248, fixed to and a part of the frontal rotation plane 242, provides the typical pitch-axis rotation, in a manner
15 similar to that discussed above. This snowshoe assembly thus provides for two degrees of rotational freedom with maximum comfort and safety to the user.

Fig. 17 shows the two desired degrees of freedom achieved in a different way. Here, a special snowshoe frame 250 is
20 deformable due to inserted rotational connections at 252 and 254. These connections can include torsion bars as connectors, such that the aggregate snowshoe frame assembly is urged back to the normal position shown in Fig. 17. A footbed 256 is secured to this snowshoe frame via a rotational cross member or binding

straps 258, preferably providing the usual pitch rotation. When the user walks on normal, flat terrain, the snowshoe frame remains essentially in the normal position as shown in the front elevation schematic of Fig. 17A. The user's boot 260 stays essentially parallel to the terrain and to the snowshoe.

However, in Fig. 17B the user has encountered a sidehill situation, and the pivoted nature of the snowshoe frame allows the footbed to assume an angular position relative to the snowshoe and to the terrain. As indicated in these schematics, the footbed 256 is allowed pivoting movement at its connections 262 to the frame, such as is permitted by binding straps 258. Thus, the snowshoe frame deflects and elastically deforms as indicated schematically in Fig. 17B, and this is reversed for the opposite sidehill situation.

Figs. 18-28 show further embodiments of the invention for achieving two degrees of rotational freedom in a snowshoe binding.

Figs. 18-20 show a molded composite snowshoe 300, molded of a plastic material with fiber filling. Figs. 18-20 are somewhat schematic, not showing all fasteners involved in order to reveal important components.

As shown in Fig. 18, the molded composite snowshoe 300 has a pair of turning engaging rails 302 that are insert molded into the plastic material. These rails are metal, preferably of

steel, such as stainless steel, and have a plurality of points 304 which act as teeth to engage the terrain. The rails may have a scalloped shape such that between the points 304 the shape of the rail bottom undulates in a curving fashion as shown at 306.

5 The metal rails 302 preferably have holes towards their upper sides, and these holes may be oval in shape, for increasing the bond with the plastic snowshoe molding by allowing the molten plastic material to flow through the holes. These holes are completely buried in the plastic and are not seen in the figures.

10 An important feature of the rails 302 is that they are curved. Each rail, as shown, has at least one curve, preferably curving inwardly toward the other rail and then back outwardly as shown in Fig. 18. In the illustrated embodiment the both ends of the rails have a short reverse curve just before the forward
15 termination point of the rail. The main curvature in the rails is important for providing fore and aft traction on hard snow or icy terrain, in addition to lateral traction and torsional traction. In addition, the curving rails provide torsional rigidity along the longitudinal axis, resisting warpage about
20 this axis.

Figs. 18 and 20 show that the metal rails may also serve the purpose of providing a pivot attachment support for a heel lift 308. The heel lift, which is to lift the user's boot heel for

steep uphill terrain, has inwardly bent ends 310 (Fig. 18) which pass through holes in the metal rails to provide the pivot support mounting. As is known, such a heel lift is normally flattened against the snowshoe deck (rotated clockwise as seen in Fig. 20), but is flipped up into the position shown in Fig. 20 when needed for steep terrain. The lift 308 can be moved forward to an "over center" position as shown, with elbows 312 resting against the snowshoe surface, to remain stable in the lifted position.

Figs. 18-20 also show an important feature of the invention whereby a footbed 314 with metal front claw 316 is suspended by cables 318 secured to the claw and to the molded snowshoe body. The flexible cable 318, which can comprise aircraft cable, is secured to the front claw 316 in an appropriate sturdy and robust manner. As indicated in these drawings, the cable is preferably secured by fasteners through the illustrated holes 320 in the footbed. Fasteners 322 are shown in Fig. 20, but are omitted for clarity in Figs. 18 and 19.

The cable binding suspension in Figs. 18-20 is in a "diamond" configuration, in which the two cables on each side are spread apart widest at their connection to the footbed, and come close together as they enter the plastic snowshoe body. The cables are under high tension, as they support the weight of the user. In Figs. 18-20, each cable enters the sides of the

snowshoe, preferably passing through holes in the metal rails 302, in a spaced apart relationship as shown. A spacing may be only a few millimeters, or up to about one centimeter or somewhat wider. The purpose of the spacing, as just seen in Fig. 19, is to provide a spring-loaded bias to the angle of the footbed relative to the snowshoe binding, on the pitch axis. As in other snowshoes of Atlas Snowshoe Company, the footbed preferably is biased in pitch to a toe-downward position as shown, and this is achieved here by the orientation of the holes 324 and 326 through which the cable passes as it enters a spring enclosure 328 at each side.

As is seen from these drawings, the metal rails 302 provide considerable strength and rigidity for this cable binding arrangement, especially as the metal rails are insert molded into the plastic of the snowshoe body.

Fig. 21 and Fig. 28 illustrate the principle of operation of the cable binding arrangement shown in Figs. 18-20. These drawings show that the cables 318 pass through the holes 324 and 326 and, on the other side of a wall 330 (which in Figs. 18-20 is the rail 302), they are subjected to spring tensioning. At the holes 324, 326 the cables may pass through a cable guide or grommet 332 seen in Fig. 19, which may be of a tough and relatively low friction plastic material, or which could be of metal. The spring, as shown in Figs. 21 and 28, preferably is a

compression spring 334 (metal or elastomer), with the cables 318 passing through the coils of the spring 334 and being secured by an end connector, such as a cable crimp device 336 bearing against a washer 338. In Fig. 28 the footpad plate or base is schematically represented at 316, with a different form of connection than what is represented in Figs. 18 and 19. In Figs. 18 and 19 the spring 334 is shown as encased in a housing 328, although this is optional. In addition, a different type of spring can be used, such as a tension spring, and this could be encased within the housing 328.

As can be seen from Figs. 21 and 28, the essentially triangular of cables 318 tends to resist any rotation of the binding in the horizontal plane, i.e. about the yaw axis. Fig. 25 also schematically indicates this effect. Both cables A and B in Fig. 25 are linked together behind the spring, and they connect to the footpad at spaced apart locations, so that such undesirable rotation is resisted.

The illustrated binding suspension provides for rotation in the roll direction about a generally centered longitudinal axis. This is an important feature for comfort, efficient use of the snowshoe on cycle terrain, and prevention of ankle injury. If the pivot point for roll-axis rotation were at left or right, the function would be quite different. Thus, if the binding footbed 314 had a hard bottom position at left and right, but each side

were allowed to tip upwardly when needed for sidehill terrain under the influence of a spring, this would not be center-axis roll rotation and would not have the benefits of the invention.

It is also seen from Fig. 21 that the holes 324, 326 through which the cables 318 pass can be spaced apart a greater distance to provide a more forceful return to the "zero" position of the footbed, since the farther these holes are separated the greater the cable-pulling force required to rotate the footbed in pitch. The holes can be aligned in an angled arrangement in the wall 330 to establish a bias pitch as discussed above, which may be in the range of roughly 10° to 30° with the binding footbed 314 toe-down relative to the snowshoe frame or body.

Fig. 22 shows a variation of Fig. 21, wherein the cables 318 pass through holes in the snowshoe body wall and then pass through an approximate 90° turn so that the springs 334 can be housed in a greater longitudinal space. This requires low-friction grommets, as at 342, and low friction cable guards or pulleys as represented at 344. Again, the compression spring 334 can be a metal coil spring or an elastomer spring. As noted above, the cables can be tensioned by a tension spring if desired, rather than a compression spring as shown. A tension spring must be anchored at a distant end from the cables, and thus tends to require somewhat more space. Such space is easily provided via an arrangement similar to Fig. 22, although a

sufficiently wide spacing between walls 330 and 330a in Fig. 22 can also accommodate tension springs.

Fig. 23 shows a variation of Fig. 21 wherein the spring force is provided by the metal rails 302a themselves. The rails 302a can be cantilevered from their insert mold areas as shown, so that a predetermined length of the metal rails (which may be of a spring steel) extends forward freely to form the cantilever. These cantilever springs could also be cantilevered plastic members.

Figs. 24A, 24B, and 24C demonstrate the rotation of the cleat-footbed 314 about the central roll axis as discussed above. In Fig. 24A, the cleat/footbed is shown schematically in a normal position, not on sidehill terrain. The springs 314 are somewhat compressed under the weight of the user bearing down on the cleat 314, and the cables 318 are shown slightly angled, approximately equally. In Fig. 24B the user has entered sidehill terrain and the cleat/footbed 314 is shown rotated in the counterclockwise direction relative to the snowshoe frame. This rotation is shown to occur generally about a central axis 346. If these are considered frontal views, the user has entered hillside terrain which slopes down to the user's left, the boot and cleat 314 remaining generally horizontal.

Fig. 24C shows the reverse situation, with the user on opposite sidehill terrain. Again, the springs 314 compress to

accommodate rotation of the cleat/footbed 314 about a generally central axis 346. This roll rotation is also referred to as rotation within the frontal plane of the user.

Fig. 26 shows a variation in which the cables 318 are not in the "diamond" configuration described relative to Figs. 18 et seq., but are generally in an "X" configuration. In this case the springs 334a, here shown as metal coil on elastomeric compression springs, are mounted on the cleat 316 of the footbed assembly 314. The cable holes 348, 350 may be provided through the side cleats 352 of the front claw or cleat 316 as shown, with the compression spring mounted immediately behind. The spacing and angular aligned relationship of the holes 348, 350 establish the strength of bias towards a normal pitch position, and the angle of bias of that normal pitch position. Here, the cables spread apart as they reach the rails or body 354 of the snowshoe. The snowshoe schematically depicted in this form of invention can be a metal rail or tubular frame snowshoe which supports a stretched decking, since the springs need not be accommodated in the peripheral areas of the snowshoe. Even the above embodiments can be incorporated on a tubular frame or rail type of snowshoe (rather than a molded composite snowshoe), but the location of the springs in the snowshoe periphery then tends to be somewhat more awkward.

The configuration shown in Fig. 26 can also be modified to a

single-hole form of suspension, in which the holes 348, 350 are replaced by a single hole. As noted above, this does not provide for biasing the footpad to a prescribed "zero" pitch angle and allows essentially pre-rotation in pitch. The single-hole form is schematically indicated in Fig. 29.

Fig. 27 shows another modification, again with the "X" configuration of cables 318, but in this case with the springs located in the snowshoe body in a manner generally similar to Fig. 22. The metal coil or elastomer compression springs 334, or tension springs, are shown positioned between molded plastic rails 358 and 360 of a molded composite snowshoe, with the spring located just beyond a bracing wall 362. Alternatively, the walls 358, 360 could be metal, as a part of a pair of metal rails 364. Again, as in Fig. 22, this arrangement provides additional space in the longitudinal direction for the spring, although low friction cable guides or pulleys are required at 366 and 368.

The above described preferred embodiments are intended to illustrate the principles of the invention, but not to limit its scope. Other embodiments and variations to this preferred embodiment will be apparent to those skilled in the art and may be made without departing from the spirit and scope of the invention as defined in the following claims.

I CLAIM: